

Epson

Mobilink™

Wireless Printer



- Battery life of up to 20-hours
- Compact size and ruggedized design
- Highest speed thermal printing in its class
- Prints labels for products, shelf tags, barcodes, mark downs, price verification, warehousing and more
- Supports 802.11b and Bluetooth™ wireless protocols
- Print width up to 54mm accommodates more text
- 60mm paper width enables use of standard off-the-shelf media
- Belt clip and shoulder strap for maximum mobility



The Mobilink wireless printer also has a label printer model for fast, on-demand printing for a wide range of label applications.

Get all the great features of Epson's best-selling TM-T88 thermal POS printer in the compact and cost-effective Mobilink wireless printer.

Built with Epson's famous quality and reliability, the Mobilink is designed to meet the needs of both retail, hospitality and logistics for uninterrupted, high-speed, on-the-go thermal receipt and label printing.

Great features go mobile

Whether you need a receipt or label printer for use in retail, hospitality, pharmacies, route accounting or distribution centers, Epson's Mobilink wireless printer comes with all the features you need. It's the fastest printer in its class and offers clear, crisp printing, drop-in paper loading and a ruggedized design to ensure reliability in even the harshest environments.

Your choice of models

With Mobilink you can have your choice of wireless interfaces. Both Mobilink's receipt printer and label printer are available with 802.11b or Bluetooth wireless protocol for fast and easy integration. The receipt printer includes an autocutter and the label printer includes a label peeler.

Best-in-class battery life

Unlike other wireless printers with an average battery life of 2-3 hours, the Mobilink features an industry-leading battery life of up to 10 hours with 802.11b models and up to 20-hours with Bluetooth models.

Compatible and ready to go

Epson's Mobilink wireless printer is compatible with today's best-of-breed and component-based POS systems and industry-standard wireless security protocols. The printer comes complete with ESC/POS®, OPOS, JPOS and Windows drivers which means your current applications are instantly compatible. Mobilink is also compatible with leading business label software applications when using Windows drivers.

Flexible wireless printing

The Mobilink comes with the required integration tools you need to easily configure the printer on site. Mobilink offers flexible, high-speed printing, labeling, network support and superior reliability with an extremely low total cost of ownership.

Epson Mobilink™ Wireless Printer

Printer Specifications

General	Print method	Thermal line printing
	Dot/line	420/432 dots
	Print font	
	Font	Font A 12 x 24, new Font B 10 x 24, new Font C 8 x 16
	Column capacity	58mm paper, Font A/B/C, 35/42/52 columns; 60mm paper, Font A/B/C, 36/43/54 columns
	Character size	1.5(W) x 3.0(H)/1.25(W) x 3.0(H)/1.0(W) x 2.0(H)mm
	Character set	95 Alphanumeric, 48 International, 128 x 10 Graphic
	Bar code	UPC-A, UPC-E, JAN8 (EAN), JAN13 (EAN), CODE 39, CODE 93, CODE 128, ITF, CODABAR, 2D bar codes: PDF417, QR CODE, MAXICODE
	Characters per inch	17/20/25 cpi

Printer	Interface	802.11b or Bluetooth (RS-232 port included)
	Data buffer	128 bytes
	Print speed (max.)	Receipt version 70mm/second, label version 80mm/second
	Paper width	Paper or labels, 58mm or 60mm width (receipt version) Paper or labels, 30–60mm (label version)
	Paper diameter (max.)	51 mm
	Autocutter	Partial cut, left uncut (receipt version)
	Peeler	Automatic label removal from backing (label version)
	Audible alert	Programmable buzzer
	Sensors	Paper out (receipt and label versions) Gap, black mark, label taken (label version)
	Indicators	Battery charge level, wireless connection status, error condition
	Software	Browser-based configuration and proprietary remote wireless management tools
	Power	Custom Lithium-Ion battery pack, AC adapter (option)
	Charging	AC adapter (4 hours to full charge), custom external charger (2.5 hours to full charge)
	Reliability	10 million printing lines 500,000 autocutter
	Operating temperature	0° C to 50° C
	Drop	4'
	Battery life	Up to 10 hours with 802.11b, up to 20 hours with Bluetooth
	Overall dimensions	103 x 159 x 65mm (W x D x H) {4.05 x 6.25 x 2.55"}
	Weight	Receipt version 670g with battery, label version 640g with battery

Control Board	EMC standards	VCCI class A, FCC class A, CE marking, AS/NZS 3548 class B
	Safety standards	UL, CSA, TÜV (EN60950)

